



COR VISION SLIDING SYSTEM

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_w from 1.3 (W/m²K)

Please consult typology, dimensions and glazing

ACCOUSTIC INSULATION

Maximum glazing: **30 mm.**

Maximum acoustic insulation: **Rw = 41 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class 7A

Wind resistance (UNE-EN 12210:2000):

Class C5

* Reference test: Balcony 1.23 x 1.55 m, 1 sash + 1 fixed

SECTIONS	Frame 116 mm Triple rail 182 mm Sash 37 mm
----------	--

EXTRUSION ALLOY

6063 T-5

PROFILE THICKNESS	Door 1.7 mm
-------------------	-------------

POLYAMIDE STRIP LENGTH

Polyamide 6.6 reinforced with 25% fiberglass from 16 to 24 mm

MAXIMUM DIMENSIONS	Width (L) = 2,200 mm Height (H) = 3,000 mm
--------------------	---

OPENING POSSIBILITIES

Sliding 2, 3, 4 and 6 sashes.
Optionally monorail and triple rail
(1 sash+1 fixed) (2 sashes+1 fixed).
Optionally corner sash at 90° without mullions.
Galandage 1 and 2 sashes

MAXIMUM WEIGHT/SASH	320 Kg
---------------------	--------

Please consult regarding maximum weight and dimensions according to types

DRAINAGE	Optionally drainage system and drainage grid made of stainless steel
----------	--

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat >60 micras

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras
Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

